



DECLARATION OF PERFORMANCE (DoP)
No. JL2020082ED
20

1.	Unique identification code of the product type	EXTERNAL DOORSETS ADVANCE-LINE – CHARACTER SBD / CED – FUNCTION SBD / ED – CLASSIC SBD / ED SIDELIGHT / SL , ECO TOPLIGHT / GPÖ
2.	Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	Non-glazed single leaf door, glazed single leaf door, Non-glazed single leaf door with Sidelight and/or Toplight, Glazed single leaf door with Sidelight and/or Toplight
3.	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer	External doorset for domestic locations
4.	Name, registered trade name or registered trademark and contact address of the manufacturer as required under Article 11 (5)	JELD-WEN Danmark A/S Danmarksvej 9 DK-9670 Løgstør Denmark www.jeld-wen.biz
5.	Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	N/A
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:	System 3
7.	In case of the declaration of performance concerning a construction product covered by a harmonized standard	SYSTEM 3: The notified laboratory, RISE Research Institutes of Sweden AB no.0402, DELTA Danish Electronics, Light and Acoustics No. 0199, assessed the performance on the basis of testing (based on sampling carried out by the manufacturer), calculation, tabulated values or descriptive documentation of the construction product and issued test-/calculation reports.

8. Declared performance			
	ADVANCE-LINE, - CHARACTER SBD, - FUNCTION SBD, - CLASSIC SBD		
	Non-glazed single leaf door 	Glazed single leaf door 	Harmonized standard
Watertightness (<i>Outswing</i>)	NPD	NPD	EN 14351-1:2006 +A2:2016
Watertightness (<i>Inswing</i>)	NPD	NPD	
Dangerous substances	None	None	
Resistance to wind load	C3	C3	
Impact resistance	N/A	NPD	
Load-bearing capacity of safety devices	N/A	N/A	
Height	NPD	NPD	
Acoustic performance	30 (-4;-4) dB	30 (-4;-4) dB	
Thermal transmittance	0,90 W/m ² K	0,97 W/m ² K	
Radiation properties g:	N/A	NPD	
Radiation properties LT:	N/A	NPD	
Air permeability	4	4	



	ADVANCE-LINE - CHARACTER SBD, - FUNCTION SBD & - CLASSIC SBD doorset with SIDE LIGHT / ECO TOPLIGHT									
	Non-glazed single leaf door				Glazed single leaf door				Harmonized standard	
	with sidelight	with toplight	with sidelight + toplight	with sidelight	with toplight	with sidelight + toplight	with toplight	with sidelight + toplight		
Watertightness	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	EN 14351-1:2006 +A2:2016
Dangerous substances	None	None	None	None	None	None	None	None	None	
Resistance to wind load	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Load-bearing capacity of safety devices	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	
Height	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Acoustic performance	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Thermal transmittance	1,5 W/m ² K	0,93 W/m ² K	1,5 W/m ² K	1,9 W/m ² K	1,3 W/m ² K	1,9 W/m ² K	1,3 W/m ² K	1,9 W/m ² K	1,9 W/m ² K	
Radiation properties g:	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Radiation properties LT:	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	
Air permeability	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	NPD	

ce



Abbreviations:

N/A = not applicable

NPD = no performance determined

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mads Storgaard Mehlsen, VP Product Management and Business Strategy for Europe

(Name and function)

Loyster, 26-03-2020

(Place and date of issue)

(Signature)