

internal doorkits

provide a flexible option; the symmetrical design of this kit system allows for handings to be decided on site, with all components ready machined... just assemble!



prepare to take the challenge.... 20 minute doorkit

Features and Benefits

- Solid reliable fixing system through the lining in to the core of the wall.
- Architrave tongue is self-adjusting to accommodate minor inaccuracies in partition widths.
- Interlocking mechanical joints for a tight accurate fit of architrave.
- Concealed fixing of lining and architrave, eliminating the need for filling and minimal preparation for decorating – in line with NHBC recommendations.
- Suitable for use with any standard JELD-WEN moulded or veneer internal door.
- MDF foil wrapped moisture resistant linings and architraves.

Specifications

Lining width options
77mm, 90mm, 95mm, 100mm, 115mm, 120mm,
125mm, 130mm, 140mm, 150mm.

Lining Thickness
25mm plus 12mm stop.
Total thickness 37mm.

Doorstop sizes
27mm and 71mm.

Architraves
Ogee, Ovolo 69mm. Torus and
Twice Rounded.

Ironmongery
65mm/55mm White Snap on hinges (dual entry).

65mm Tubular latch, 65mm bath lock
Electro Brass or Bright Polished Steel.

Glazed doors have solid stiles and rails and are
supplied pre-glazed. Glazed fire doors are also available.



ready fit doorkits

prepare to take the doorkit challenge....

Install in just 20 minutes

What's in the Kit?

Door prepared and fitted with 3 hinges and latch
Lining leg prepared and fitted with 3 hinges
Lining leg prepared and fitted with strike plate
Lining head machined and drilled for assembly
Doorstops to suit lining
2 x furniture bolts to fix product together
Pack of architrave, mitred, to suit both sides of lining.

FD30 and bath locks optional extras

JELD-WEN UK Ltd
Watch House Lane Doncaster
South Yorkshire DN5 9LR
T. 0870 126 0000 F. 01302 787 383
E. marketing@jeld-wen.co.uk
E. customer-services@jeld-wen.co.uk

JELD-WEN
WINDOWS & DOORS

visit us at www.jeld-wen.co.uk

MFD49 ISSUE A SEP 06

JELD-WEN
WINDOWS & DOORS



1. Decide on handing then assemble frame using bolts provided



2. Adjustable snap on hinges (male) provided fixed to lining leg



3. To reverse handing remove and turn hinge 180° to re-fix



4. Keep is provided fixed to the lining



5. To reverse handing remove and turn latch 180° to re-fix



6. Ensure frame is square and plumb



7. Remove 'grommit' in door hinge which allows frame hinge to locate re position 'grommit' when in place



8. Offer door to frame and locate the hinge, re-fix 'grommit'



9. Fit and Fix architraves in place
10. Fit and Fix door stops in place