



Declaration of Performance	
DoP No. JL2022125ED-UK	
22	

Unique identification code	EXTERNAL DOORSETS				
of the product-type:	$1 \Delta 11 V \Delta M = 1 M = E (1) SR 1 dOOr$				
	Non-glazed single leaf door, glazed single leaf door				
Type:	with Sidelight and/or Toplight				
Intended use:	External door for domestic locations and commercial locations				
Manufacturer:	JELD-WEN Danmark A/S, Danmarksvej 9, DK-9670 Løgstør, Denmark www.jeld-wen.biz				
Authorised representative:	JELD-WEN UK LTD. Retford Road, Woodhouse Mill, Sheffield, South Yorkshire, S13 9WH, United Kingdom				
	AVCP	Approved Test Laboratory /	Designated		
	System	Approved Body. No.	standard		
		A = RISE Research Institutes of Sweden AB / No. 0402			
		B = N/A			
Systems of Assessment and Verification of Constancy of Performance (AVCP)	3	C = N/A	EN 14351-1:2006 +A2:2016		
		D = N/A			
		E = N/A			





Decla	red performances			
		ADVANCE-LINE ECO SBD		
		Non-glazed single leaf door	Glazed single leaf door	Test laboratory
	Watertightness (Outswing)	4A	4A	Α
	Watertightness (Inswing)	3A / 7B ¹⁾	3A / 7B ¹⁾	Α
	Dangerous substances	None	None	
	Resistance to wind load	C3	C3	Α
3	Impact resistance	N/A	NPD	-
AVCP System	Load-bearing capacity of safety devices	N/A	N/A	-
	Height	NPD	NPD	-
	Acoustic performance	NPD	NPD	-
	Thermal transmittance	0.66 W/m²K	0.81 W/m²K	А
	Radiation properties g:	N/A	NPD	-
	Radiation properties LT:	N/A	NPD	-
	Air permeability	4	4	Α





Declar	ed performances							
		ADVANCE-LINE ED SBD door with ECO SIDELIGHT / ECO TOPLIGHT						
		Non-glazed single leaf door		Glazed single leaf door				
		with sidelight	with toplight	with sidelight + toplight	with sidelight	with toplight	with sidelight + toplight	atory
		T.				<i>a</i>		Test labora
	Watertightness (Outswing)	NPD	NPD	NPD	NPD	NPD	NPD	-
tem 3	Dangerous substances	None	None	None	None	None	None	-
	Resistance to wind load	NPD	NPD	NPD	NPD	NPD	NPD	-
	Impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	-
	Load-bearing capacity of safety devices	N/A	N/A	N/A	N/A	N/A	N/A	-
Sys	Height	NPD	NPD	NPD	NPD	NPD	NPD	-
/CP	Acoustic performance	NPD	NPD	NPD	NPD	NPD	NPD	-
₹ T	Thermal transmittance	0.78 W/m ² K	0.72 W/m ² K	0.83 W/m ² K	0.94 W/m ² K	0.88 W/m ² K	0.98 W/m ² K	Α
	Radiation properties g:	NPD	NPD	NPD	NPD	NPD	NPD	-
	Radiation properties LT:	NPD	NPD	NPD	NPD	NPD	NPD	-
	Air permeability	NPD	NPD	NPD	NPD	NPD	NPD	-

JEILD WEN.



Abbreviations:

N/A = not applicable NPD = no performance determined

 $^{1)}$ = 7B is only valid when mounted with a drop plate

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nigel Dilks,
VP Product Management, Europe
(Name and function)

(Place and date of issue)

20.12.2022.

Solihull.

West Mallands.