

# MODA

## Interior Doors



- **Design your own door**

Express your style by creating your own bar design, or follow one of the popular design guides provided.

- **Sound performance**

Featuring a solid core for improved durability and enhanced sound insulation over a lightweight alternative, for added privacy throughout the home.

- **Charming simplicity**

Each door is supplied factory primed for a smooth minimalist aesthetic that can't be overlooked. Its boldness lies in its simplicity.



MIN 2 PERSON LIFT

# CURATED

by **JELD-WEN**.

# INSTALLATION, FINISHING AND CARE INSTRUCTIONS

## INTRODUCTION

JELD-WEN MODA doors are of an engineered construction, with white primed HDF faces to provide great stability and durability. Timber is a natural and sustainable product which, if properly treated and maintained, is protected from natural changes in humidity and temperature found in an internal environment. If however MODA doors are not correctly stored, installed, finished and maintained in accordance to the guidance provided, problems can occur due to movement or distortion, such as swelling, shrinking, warping or splitting.

Prior to finishing, hanging and installation of bars, inspect for damage and defects, DO NOT proceed to work if any noticeable damage or defect is evident. Finishing and/or installation of the door constitutes acceptance of aesthetic quality.

## IMPORTANT

- Doors must be stored flat on three level bearers and kept dry at all times
- Avoid direct contact with sunlight before the door has been finished
- Do not install or store the door in newly plastered rooms
- Polythene wrapping should remain on the doors until immediately before finishing and installing
- Check the door for defects or damage before installation - DO NOT continue to install the door if any defects or damage are found
- Any small nicks or scratches should be sanded using fine sandpaper before finishing
- Any door which has been modified cannot be exchanged, except doors with proven manufacturing defects
- Doors should be handled carefully with clean gloves and not dragged across each other or across other surfaces
- Doors must be sealed on both faces and ALL edges prior to installation
- Claims for twisting, bowing, shrinking, or swelling that are moisture related (while the doors are not sealed according to our guidelines) will be rejected.

## TRIMMING/INSTALLATION

JELD-WEN MODA doors can be reduced in size by a maximum of 10mm in width (Max 5mm per side) and 6mm in height, removed from the bottom edge. We recommend that an equal amount is trimmed from either side of the door to maintain a balanced appearance. We do not recommend trimming the top edge of the door, as this removes the doors traceability print used for warranty purposes.

JELD-WEN recommend as a minimum three 76mm (3") hinges for interior doors. Whilst checking the size in the door frame, mark hinge positions and any levers or locks you wish to attach to the door.

JELD-WEN MODA doors are supplied with loose, self adhesive bars, to provide you with the flexibility to create your own design to match your style. Please follow the "Bar Installation" sheet on how to correctly install the bars provided.

## FINISHING

It is essential that the door is completely finished on the two faces and all FOUR edges, plus within any cut-outs for locks, handles and hinges. Plant on bars must also be finished on all exposed faces and care must be taken not to paint over the adhesive tape on the rear of the bar. Prior to finishing or sealing, lightly sand any handling marks. Do not use wire wool or other sanding materials containing steel or iron on our doors.

MODA doors are supplied pre primed and will require to be finished with a proprietary branded paint. We strongly recommend that you finish this door in accordance with the paint manufacturers instructions.

MODA Glazed doors are supplied with a protective paint and peel film, applied to both sides of the glass. This will need to be carefully removed once the door has been finished.

A light sanding between coats will provide the best finish. Adequate drying time must be allowed between each coat. Failure to seal the doors accordingly will invalidate any claims.

**Note:** Polishes, waxes, oils or dyes should not be used on these doors.

## MAINTENANCE

Regular maintenance of this door should be made in accordance with the paint manufacturer's instructions, to prevent breakdown of the wood finish and to protect the timber from deterioration. Use a damp cloth to routinely wipe clean the doors surface, and ensure to touch up any exposed areas of timber with a suitable colour matched paint.

## CONDITIONS OF SALE

JELD-WEN will not be held responsible for any incidental work or problems as a result of bad storage, handling or incorrect fitting and finishing of our doors. The foregoing does not affect your statutory rights.



Many doors weigh over 18kg and may require consideration when handling



MAY CONTAIN GLASS  
The glass used in glazed products meets the requirements of BS6206 or EN12150.