

MOULDED PANEL

HALF GLAZED STANDARD CORE

– INTERNAL DOOR

SPECIFICATIONS

Construction

Moulded wood fibre face with softwood stiles and rails.
Tubular chipboard inner stiles. Glazed with 4mm toughened glass.

Door Codes

WOODGRAIN:	Bostonian & Oakfield 6 Light Etch	APHOFD+SE
	Camden 6 Light Etch	APHCMN+SE
	Newark 6 Light Etch	APHNEWA+SE
	Atherton 6 Light Etch	APHATH+SE
SMOOTH:	Arlington 6 Light Etch	APHARL+SE
	Cambridge 6 Light Etch	APHCAMB+SE

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.0mm die-formed wood fibre skin.

Components

Stiles:	Softwood min 28mm (nominal width)
Rails:	Softwood min 28mm (nominal width)
Glazing Framing:	Polystyrene and softwood min 28mm (nominal width)
Glazing Cassette:	Foil wrapped MDF*, PVC
Core:	Cellular with 55mm chipboard strips to stiles
Lockblock:	N/A
Lipping:	N/A

*Camden glazed only

Lock Area

Locks and handles may be fitted centrally in height either side of the door.

Finish

Supplied white primed for paint finish on site.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door should not be trimmed due to the manufacturing identifications.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

