

MOULDED PANEL

2 LIGHT GLAZED BI-FOLD STANDARD CORE – INTERNAL DOOR

SPECIFICATIONS

Construction

Moulded wood fibre face with softwood stiles and rails.
Standard polystyrene pad core.

Door Codes

Woodgrain:

Clear APBIOF+GCF
Etch APBIOF+ET

Arlington smooth:

Clear APBIAR+GCF
Etch APBIAR+ET

Atherton smooth:

Clear APBIAT+GCF
Etch APBIAT+ET

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.0mm die-formed moulded wood fibre skin.

Components

Stiles: Softwood min 28mm (nominal width)
Rails: Softwood min 28mm (nominal width)
Rails Inner: Softwood min 28mm (nominal width)
Mid Rail: Double softwood min 28mm (nominal width)
Core: Cellular
Lockblock: N/A
Lipping: N/A

Lock Area

Handles may be fitted to the mid rail area.

Finish

Supplied white primed for paint finish on site.

Maximum Trim

Bifold doors are not recommended for trimming.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door. Lubricate hinges and metal moving parts annually. Re-decorate the door as necessary always following the paint manufacturer's instructions.

