SLIM-LINE Interior Doors



The perfect statement door for modern apartments and homes with design at their hearts.

• Well-lit living

This slim & sleek design allows light to flood into a room, creating a warm and inviting environment.

Style and substance

A high end, contemporary design, offering the same modern feel of a sleek aluminum door in a timber alternative.





INSTALLATION, FINISHING AND CARE INSTRUCTIONS

INTRODUCTION

JELD-WEN SLIM-LINE doors are constructed from engineered pine & HDF faces to provide great stability and durability. Timber is a natural and sustainable product which, if properly treated and maintained, is protected from natural changes in humidity and temperature found in an internal environment. If however SLIM-LINE doors are not correctly stored, installed, finished and maintained in accordance to the guidance provided, problems can occur due to movement or distortion, such as swelling, shrinking, warping or splitting.

Prior to hanging this door, inspect for damage and defects, DO NOT proceed to work on it if any noticeable damage or defect is evident. Finishing and/or installation of the door constitutes acceptance of aesthetic quality.

IMPORTANT

- Doors must be stored flat on three level bearers and kept dry at all times
- · Do not install or store the door in newly plastered rooms
- Polythene wrapping should remain on the doors until immediately before finishing and installing
- Check the door for defects or damage before installation DO NOT continue to install the door if any defects or damage are found
- Any door which has been modified cannot be exchanged, except doors with proven manufacturing defects
- Doors should be handled carefully with clean gloves and not dragged across each other or across other surfaces
- Doors must be sealed on ALL edges prior to installation
- Claims for twisting, bowing, shrinking, or swelling that are moisture related (while the doors are not sealed according to our guidelines) will be rejected.

TRIMMING/INSTALLATION

SLIM-LINE doors can be reduced in size by a maximum of 10mm in width (Max 5mm per side) and 6mm in height, removed from the bottom edge. We recommend that an equal amount is trimmed from either side of the door to maintain a balanced appearance. We do not recommend trimming the top edge of the door, as this removes the doors traceability print used for warranty purposes.

JELD-WEN recommend hanging this door using a minimum of 3 76mm (3") hinges.

SLIM-LINE doors are suitable for use with Roller or Ball catches that do not encroach more than 50mm into the door before trimming. We also recommend the use of pull handles with appropriately spaced fixing centres to fit within the 24 down to before the true is the door before the part of the space o

within the 240mm lock area shown in the diagram below. Due to the narrow stiles used within this door design, these doors are not suitable for use with traditional 65mm length tubular latches and lever handles.

FINISHING

These doors are fully finished and ready to hang. You may need to decorate the edges if trimming is required during installation with a suitable colour matched, matt finish interior paint. When choosing a suitable colour matched paint, you may wish to use the following colour references to aid your selection – Black RAL 9011 or Grey RAL 7046.

MAINTENANCE

Regular maintenance of this door should be made, to prevent breakdown of the wood finish and to protect the timber from deterioration. Use a damp cloth to routinely wipe clean the doors surface, and ensure to touch up any exposed areas of timber with a suitable colour matched paint.

CONDITIONS OF SALE

JELD-WEN will not be held responsible for any incidental work or problems as a result of bad storage, handling or incorrect fitting and finishing of our doors. The foregoing does not affect your statutory rights.



Many doors weigh over 18kg and may require consideration when handling



MAY CONTAIN GLASS The glass used in glazed products meets the requirements of BS6206 or EN12150.

