



Declaration of Performance	
DoP No. JL2022126ED-UK	
22	

Unique identification code	EXTERNAL FIRE DOORSETS								
of the product-type:	ADVANCE-LINE ECO SBD								
or the product type.	ECO SIDELIGHT, ECO TOPLIGHT								
T. (D. C.	Non-glaze	ed single leaf door, glazed single leaf door							
Type:	with/with	nout Sidelight and/or Toplight							
Intended use:	1	oorset for fire and/or smoke compartmentation and/o and commercial locations	r escape routes in						
Manufacturer:		ELD-WEN Sverige AB, Förrådsgatan, SE - 265 81 ÅSTORP, Sweden ww.jeld-wen.biz							
Authorised representative:	JELD-WEN Retford Ro	I UK LTD. oad, Woodhouse Mill, Sheffield, South Yorkshire, S13 9	WH, United Kingdom						
SYSTEM 1: Certificate of constancy of performance	- an asses basis of docume initial in	Approved product certification body DBI Certification UK Ltd. no. 8504 carried out: an assessment of the performance of the construction product carried out on the basis of testing (including sampling), calculation, tabulated values or descriptive documentation of the product. initial inspection of the manufacturing plant and of factory production control continuing surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance of the product.							
	0.11011000	Jed the certificate of constancy of performance of the	product						
	AVCP System	Approved Body. No.	product.  Designated  standard						
	AVCP	Approved Test Laboratory /	Designated						
	AVCP	Approved Test Laboratory / Approved Body. No.  A = DBI Dansk Brand- og Sikringsteknisk Institut /	Designated standard						
Systems of Assessment and	AVCP	Approved Test Laboratory / Approved Body. No.  A = DBI Dansk Brand- og Sikringsteknisk Institut / No. 0845	Designated standard						
Verification of Constancy of	AVCP	Approved Test Laboratory / Approved Body. No.  A = DBI Dansk Brand- og Sikringsteknisk Institut / No. 0845  B = N/A  C = RISE Research Institutes of Sweden AB /	Designated standard						
	AVCP	Approved Test Laboratory / Approved Body. No.  A = DBI Dansk Brand- og Sikringsteknisk Institut / No. 0845  B = N/A  C = RISE Research Institutes of Sweden AB / No. 0402	Designated standard						
Verification of Constancy of	AVCP	Approved Test Laboratory / Approved Body. No.  A = DBI Dansk Brand- og Sikringsteknisk Institut / No. 0845  B = N/A  C = RISE Research Institutes of Sweden AB / No. 0402  D = N/A	Designated standard  EN 16034:2014  EN 14351-1:2006						





Jecla	red performances					
			ADVANCE-LINE 8	ECO SBD		
		Non-glazed single leaf door	Glazed single leaf door	Non-glazed single leaf door	Glazed single leaf door	Test lahoratory
	Resistance to fire	EI <sub>1</sub> 30	El <sub>1</sub> 30	El <sub>1</sub> 30	El <sub>1</sub> 30	A
stem 1	Smoke control	NPD	NPD	S <sub>200</sub>	S <sub>200</sub>	A
	Ability to release	NPD	NPD	NPD	NPD	-
	Self-closing	NPD	NPD	NPD	NPD	-
P Sy	Durability of ability to release	NPD	NPD	NPD NPD		-
4VC	Durability of self-closing					
1	- against degradation (cycling testing)	NPD	NPD	NPD	NPD	-
	- against ageing (corrosion)	NPD	NPD	NPD	NPD	-
	Watertightness (Outswing)	4A	4A	4A	4A	C
	Watertightness (Inswing)	3A / 7B <sup>1)</sup>	3A / 7B <sup>1)</sup>	3A / 7B <sup>1)</sup>	3A / 7B <sup>1)</sup>	C
	Dangerous substances	None	None	None	None	_
	Resistance to wind load	C3	C3	C3	C3	C
m 3	Impact resistance	NPD	NPD	NPD	NPD	-
/ste	Load-bearing capacity of safety devices	N/A	N/A	N/A	N/A	-
P Sy	Height	NPD	NPD	NPD	NPD	-
٩VC	Acoustic performance	NPD	NPD	NPD	NPD	-
	Thermal transmittance	0.81 W/m²K	0.81 W/m²K	0.81 W/m²K	0.81 W/m²K	C
	Radiation properties g:	NPD	NPD	NPD	NPD	-
	Radiation properties LT:	NPD	NPD	NPD	NPD	
	Air permeability	4	4	4	4	C

## JEID WEN.



Decla	red performances							
			ADVANCE-	LINE ECO SBD door wit	h ECO SIDELIGHT / EC	O TOPLIGHT		
		Non-glazed single leaf door			Glazed single leaf door			
		with sidelight	with toplight	with sidelight + toplight	with sidelight	with toplight	with sidelight + toplight	ratory
		ic .						Test labo
	Resistance to fire	EI <sub>1</sub> 30	EI <sub>1</sub> 30	EI <sub>1</sub> 30	EI <sub>1</sub> 30	El <sub>1</sub> 30	EI <sub>1</sub> 30	Α
	Smoke control	NPD	NPD	NPD	NPD	NPD	NPD	Α
m 1	Ability to release	NPD	NPD	NPD	NPD	NPD	NPD	-
/ste	Self-closing	NPD	NPD	NPD	NPD	NPD	NPD	-
P S	Durability of ability to release	NPD	NPD	NPD	NPD	NPD	NPD	-
AVC	Durability of self-closing							
	- against degradation (cycling testing)	NPD	NPD	NPD	NPD	NPD	NPD	-
	- against ageing (corrosion)	NPD	NPD	NPD	NPD	NPD	NPD	-
	Watertightness (Outswing)	NPD	NPD	NPD	NPD	NPD	NPD	-
	Dangerous substances	None	None	None	None	None	None	-
	Resistance to wind load	NPD	NPD	NPD	NPD	NPD	NPD	
3	Impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	-
tem	Load-bearing capacity of safety devices	N/A	N/A	N/A	N/A	N/A	N/A	-
Syst	Height	NPD	NPD	NPD	NPD	NPD	NPD	-
/CP	Acoustic performance	NPD	NPD	NPD	NPD	NPD	NPD	-
A	Thermal transmittance	0.78 W/m <sup>2</sup> K	0.72 W/m <sup>2</sup> K	0.83 W/m <sup>2</sup> K	0.94 W/m <sup>2</sup> K	0.88 W/m²K	0.98 W/m <sup>2</sup> K	С
	Radiation properties g:	NPD	NPD	NPD	NPD	NPD	NPD	-
	Radiation properties LT:	NPD	NPD	NPD	NPD	NPD	NPD	-
	Air permeability	NPD	NPD	NPD	NPD	NPD	NPD	-

## 



	red performances							
		ADVANCE-LINE ECO SBD door with ECO SIDELIGHT / ECO TOPLIGHT						
			on-glazed single leaf d	loor Glazed single leaf door			r	
		with sidelight	with toplight	with sidelight + toplight	with sidelight	with toplight	with sidelight + toplight	
		i.C	ij.				in the second se	
	Resistance to fire	EI <sub>1</sub> 30	EI <sub>1</sub> 30	EI <sub>1</sub> 30	EI <sub>1</sub> 30	El <sub>1</sub> 30	El <sub>1</sub> 30	+
$\leftarrow$	Smoke control	S <sub>200</sub>	S <sub>200</sub>	S <sub>200</sub>	S <sub>200</sub>	S <sub>200</sub>		
em	Ability to release	NPD	NPD	NPD	NPD	NPD	S <sub>200</sub> NPD	
Syst	Self-closing	NPD	NPD	NPD	NPD	NPD	NPD	-
<u>C</u>	Durability of ability to release	NPD	NPD	NPD	NPD	NPD	NPD	+
A	Durability of self-closing						INFL	
	- against degradation (cycling testing)	NPD	NPD	NPD	NPD	NPD	NPD	
	- against ageing (corrosion)	NPD	NPD	NPD		NPD	NPD NPD	
	Watertightness (Outswing)	NPD	NPD	NPD	NPD	NPD		+
	Dangerous substances	None	None	None	None	None	NPD	
	Resistance to wind load	NPD	NPD	NPD	NPD	NPD	None	
ک (	Impact resistance	NPD	NPD	NPD	NPD	NPD	NPD	
sten	Load-bearing capacity of safety devices	N/A	N/A	N/A	N/A	N/A	NPD N/A	-
So I	Height	NPD	NPD	NPD	NPD	NPD	N/A	-
2	Acoustic performance	NPD	NPD	NPD	NPD	NPD	NPD	-
	Thermal transmittance	0.78 W/m <sup>2</sup> K	0.72 W/m <sup>2</sup> K	0.83 W/m <sup>2</sup> K	0.94 W/m <sup>2</sup> K	0.88 W/m <sup>2</sup> K	NPD 0.00 M// 31/	
	Radiation properties g:	NPD	NPD	NPD	NPD	NPD	0.98 W/m <sup>2</sup> K	
	Radiation properties LT:	NPD	NPD	NPD	NPD		NPD	
	Air permeability	NPD	NPD	NPD	NPD	NPD NPD	NPD NPD	

## JEILD WEN



Abbreviations:

N/A = not applicable NPD = no performance determined

 $^{1)}$  = 7B is only valid when mounted with a drop plate

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Nigel Dilks,
VP Product Management, Europe
(Name and function)

(Place and date of issue) (Signature)

20.12.2022.

Eclibull. West Modlands.