

# Kitemark™ Certificate

This is to certify that:

Jeld-Wen UK Ltd  
Snow Hill  
Melton Mowbray  
LE13 1PD  
United Kingdom

Holds Certificate Number:

KM 648375

In respect of:

**BS 644 / PAS 24**  
**Enhanced Security Timber Door Fabricator**

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:

Frank Lee, Product Certification Technical and Compliance Director

First Issued: 2016-04-19

Latest Issue: 2021-12-10

Effective Date: 2021-12-12

Expiry Date: 2024-12-11

Page: 1 of 4



...making excellence a habit.™

# Kitemark™ Certificate

No. KM 648375

## BS 644:2012 / PAS 24:2016 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the fabrication of doors to the following system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### DreamVu Residential Door System

Fabricated and installed in accordance with the latest issue of the following manual(s):  
JELD-WEN UK Ltd Enhanced Security Schedule of Components

**Material:** European Redwood

### System description:

The door assemblies are open in or open out, hinged on outer frame, externally beaded with BS EN 1279-2 compliant IGU(s) laminated on one pane to Class P1A. Hardware ERA GHS lock & hinge HG200, Stormguard Aluminium threshold. Doors are classified D.

### Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Dimensions for doors with approved outer frame and sash profiles:						
Single leaf open out	1054	2088	3	2A	C3	800X
Single leaf open in	1054	2088	2	2A	C2	800X
Double leaf open out	1788	2088	3	2A	C3	800X
Double leaf open in	1788	2088	3	3A	C2	800
Double leaf open out with sidights	2988	2088	3	2A	C3	800X

First Issued: 2016-04-19  
Latest Issue: 2021-12-10

Effective Date: 2021-12-12  
Expiry Date: 2024-12-11

Page: 2 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

# Kitemark™ Certificate

No. KM 648375

## BS 644:2012 / PAS 24:2016 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the fabrication of doors to the following system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### Farndale/Canberra/Darwin Residential Door Systems

Fabricated and installed in accordance with the latest issue of the following manual(s):  
JELD-WEN UK Ltd Enhanced Security Schedule of Components

**Material:** European Redwood, Red Grandis and European Oak

### System description:

The door assemblies are open in or open out, hinged on outer frame, externally beaded with BS EN 1279-2 compliant IGU(s) laminated on one pane to Class P1A. Hardware ERA GHS lock & hinge HG200, Stormguard Aluminium threshold. Doors are classified D.

### Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Dimensions for doors with approved outer frame and sash profiles:						
Single leaf open in	1026	2088	3	3A	C3	800
Single leaf open out	1026	2088	4	2A	C2	800X
Double leaf open in	1788	2088	3	3A	C3	800
Double leaf open out	1788	2088	4	2A	C2	800X
Double leaf open in with sidelight & opening vent	2388	2088	3	3A	C3	800
Double leaf open in with sidelight & opening vent	2988	2088	-	-	-	800
Double leaf open out with sidelight & opening vent	2388	2088	3	3A	C3	800

First Issued: 2016-04-19

Latest Issue: 2021-12-10

Effective Date: 2021-12-12

Expiry Date: 2024-12-11

Page: 3 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

# Kitemark™ Certificate

No. KM 648375

## BS 644:2012 / PAS 24:2016 - General and enhanced security performance requirements for door assemblies.

This Certificate covers the fabrication of doors to the following system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

### Timber Panel Residential Door System

Fabricated and installed in accordance with the latest issue of the following manual(s):  
JELD-WEN UK Ltd Enhanced Security Schedule of Components

**Material:** Red Grandis, European Redwood and Okoume

### System description:

The door assemblies are open in only, hinged on outer frame, externally beaded with BS EN 1279-2 compliant IGU(s) laminated on one pane to Class P1A. Hardware ERA GHS lock & hinge HG200, Stormguard Aluminium threshold, with letterplate. Doors are classified D.

### Size Limitations and Performance Characteristics

Door Type	Length (mm) - Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Dimensions for doors with approved outer frame and sash profiles:						
Single leaf open in	1090	2460	4	2A	C4	800X
Single leaf open out	1090	2460	4	2A	C4	800X

First Issued: 2016-04-19  
Latest Issue: 2021-12-10

Effective Date: 2021-12-12  
Expiry Date: 2024-12-11

Page: 4 of 4

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).