

For further information
on our full range of stairs,
windows and doors visit
www.jeld-wen.co.uk



making moving easier
with **JELD-WEN**



Balustrade
system that
allows free
movement

SSIME/JWS1480/NOV12

You have purchased a JELD-WEN stair fitted with a revolutionary demountable balustrade system.

This guide will help you to utilise the system giving you ease of access to the stair well.

EASY TO FOLLOW INSTRUCTIONS FOR DEMOUNTABLE BALUSTRADE SYSTEM

1. Prepare: you will need a screwdriver (Phillips & flat head) and spanner



5. After completing this task at both ends of the balustrade, unscrew the floor rail



9. Hold the newel top, loosen the nut and remove newel top



2. Remove the cover caps from the newel to expose fitting bolt for the handrail



6. Once all bolts are removed and floor rail unscrewed, carefully lift off the assembled balustrade



10. To reassemble follow instructions in reverse


3. Unscrew the bolt using your screwdriver



7. This will leave behind the end spindles, these can be simply lifted off their dowel pegs



11. Ensure the handrail bolt locates in the end cap correctly otherwise the hand rail will not relocate squarely



4. Remove the bolt and keep safely



8. This now leaves the newel tops to be removed, remove cover caps from rear of newel to expose fitting



12. Also, carefully re-locate the loose end spindles into the groove on the underside of the hand rail assembly

CAUTION: the demountable balustrade option should only be used as a temporary measure for the moving of furniture and other such large items, the stairwell should be protected to prevent accidents. You should carry out your own risk assessment before using this facility to ensure safety at all times.