

# REAL WOOD VENEER

## FD60 54mm

### – INTERNAL FIRE DOOR

#### SPECIFICATIONS

##### Fire Rating

FD60 54mm 60minute to BS476:Part 22: 1987 (CERTIFIRE CF331).

##### Construction

Flush face with complementing hardwood lippings to two edges.  
Over veneered with a streboard core.

##### Door Codes

Ash	ASHOVFD	White Oak Inlay	WOK1PFD
Beech	BCHOVFD	White Oak Fusion	WOKHVSFD
Koto	KOTOVFD	Walnut Fusion	WALHVSFD
Sapele	SAPOVFD		
White Oak	WOKOVFD		
Walnut	WALOVFD		

##### Moisture Content

10% (+/-2%) in accordance with BS:EN942.

##### Facings

0.6mm real wood veneer.

##### Components

Stiles:	N/A
Rails (outer):	N/A
Rails (inner):	N/A
Core:	Streboard
Lockblock:	N/A
Lipping:	10mm hardwood complementing in colour

##### Lock Area

Locks and handles may be fitted centrally in height either side of the door.

##### Finish

Fully finished no further decoration required to the two faces, finish the four edges with clear lacquer or varnish after trimming.

##### Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge.  
The top of the door is not allowed to be trimmed due to the BWF-Certifire fire certification label and manufacturing identifications.

##### Installation Note

The doors have been tested to BS476 pt 22:1987 and are approved by BWF-Certifire of being capable of achieving 60 minute fire resistance when fitted in accordance with the installation instruction delivered with every door.

All doors must be fitted with intumescent strips to the top and sides of the door leaf or frame.

Cutting of apertures or glazing on site is not permitted and invalidates the fire certification. Third party BWF-Certifire licensed processors are able to complete this ancillary work when required.

##### Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

