

REAL WOOD VENEER

SELECTION HEAVYWEIGHT CORE 4 LIGHT GLAZED – INTERNAL DOOR

SPECIFICATIONS

Construction

Flush face with softwood stiles and rails and complementing hardwood lippings. Over veneered with a flaxboard core. Glazed with 4mm clear toughened glass.

Door Codes

White Oak Inlay	WOK1PSC4+GCF
Silver Ash Inlay	SASH1PSC4+GCF
Brown Ash Inlay	BASH1PSC4+GCF
White Oak Twin Inlay	WOKTWISC4+GCF

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.2mm veneered wood fibre board.

Components

Stiles:	Softwood min 28mm (nominal width)
Rails (outer):	Softwood min 28mm (nominal width)
Rails (inner):	Chipboard min 38mm (nominal width)
Core:	Flaxboard
Lockblock:	N/A
Lipping:	6mm hardwood complementing in colour

Lock Area

Locks and handles maybe fitted centrally in height either side of the door.

Finish

Fully finished no further decoration required to the two faces, finish the four edges with clear lacquer or varnish after trimming.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door should not be trimmed due to the manufacturing identifications.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

