

# REAL WOOD VENEER

## SELECTION HEAVYWEIGHT CORE

### – INTERNAL DOOR

#### SPECIFICATIONS

##### Construction

Flush face with softwood stiles and rails and complementing hardwood lippings. Over veneered with a flaxboard core.

##### Door Codes

White Oak Fusion	WOKHVSSC
Walnut Fusion	WALHVSSC
White Oak Inlay	WOK1PSC
Olive Ash Fusion	OASHHVSSC
Grey Fusion	GOAKHVSSC
White Oak Twin Inlay	WOK1PSC
Walnut 4 Panel Inlay	WAL4PSC
Silver Ash Inlay	SASH1PSC
Brown Ash Inlay	BASH1PSC
Textured White Oak	WOKTEXSC
Textured Grey Oak	GOAKTEXSC

##### Moisture Content

10% (+/-2%) in accordance with BS:EN942.

##### Facings

3.2mm veneered wood fibre board.

##### Components

Stiles:	Softwood min 28mm (nominal width)
Rails (outer):	Softwood min 28mm (nominal width)
Rails (inner):	Chipboard min 38mm (nominal width)
Core:	Flaxboard
Lockblock:	N/A
Lipping:	6mm hardwood complementing in colour

##### Lock Area

Locks and handles maybe fitted centrally in height either side of the door.

##### Finish

Fully finished no further decoration required to the two faces, finish the four edges with clear lacquer or varnish after trimming.

##### Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door should not be trimmed due to the manufacturing identifications.

##### Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

