

REAL WOOD VENEER

STANDARD CORE

– INTERNAL DOOR

SPECIFICATIONS

Construction

Flush face with softwood stiles and rails with complementing hardwood lippings. Over veneered with a cellular core.

Door Codes

Ash	ASHOV
Beech	BCHOV
Koto	KOTOV
Sapele	SAPOV
Walnut	WALOV
White Oak	WOKOV

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.2mm veneered wood fibre board.

Components

Stiles:	Softwood min 28mm (nominal width)
Rails:	Softwood min 28mm (nominal width)
Core:	Cellular
Lockblock:	Chipboard
Lipping:	6mm hardwood complementing in colour

Lock Area

A lock-block is positioned centrally to one side of the door which is indicated by the word "LOCK" to the top edge. This is an area of 320mm high x 55mm wide.

Finish

Fully finished no further decoration is required to the faces, finish the four edges with clear lacquer or varnish after trimming.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge.

The top of the door should not be trimmed due to the manufacturing identifications.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

