

MOULDED PANEL

FD30 44mm

– INTERNAL FIRE DOOR

SPECIFICATIONS

Fire Rating

FD30 44mm 30minute to BS476:Part 22: 1987 (CERTIFIRE CF160 & CF192).

Construction

Moulded wood fibre face with softwood stiles and rails.
FD30 flaxboard or tubular chipboard core.

Door Codes

Arlington 6 panel smooth (enhanced bead detail)	ARLF
Atherton 4 panel smooth	ATHF
Bostonian 6 panel woodgrain	BTNF
Cambridge 2 panel smooth	CAMBF
Camden 2 panel woodgrain	CMNF
Oakfield 4 panel woodgrain	OFDF
Rockport® 5 panel smooth	ROCKF
Newark woodgrain	NEWAF
Linea smooth	LINEF
Cube smooth	CUBEF
Newbridge smooth	NEWBBF

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.0mm die-formed moulded wood fibre skin.

Components

Stiles:	Softwood min 38mm (nominal width)
Rails (outer):	Softwood min 32mm (nominal width)
Rails (inner):	Chipboard min 38mm (nominal width)
Core:	Flaxboard or tubular chipboard
Lockblock:	N/A
Lipping:	N/A

Lock Area

Locks and handles may be fitted centrally in height either side of the door, maximum dimensions specified on installation instructions provided.

Finish

Supplied white primed for paint or stain finish on site.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge.
The top of the door is not allowed to be trimmed due to the BWF-Certifire fire certification label and manufacturing identifications.

Installation Note

The doors have been tested to BS476 pt 22:1987 and are approved by BWF-Certifire of being capable of achieving 30 minute fire resistance when fitted in accordance with the installation instruction delivered with every door.

All doors must be fitted with intumescent strips to the top and sides of the door leaf or frame.

Cutting of apertures or glazing on site is not permitted and invalidates the fire certification.

Third party BWF-Certifire licensed processors are able to complete this ancillary work when required.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

