

MOULDED PANEL

FD60 54mm

– INTERNAL FIRE DOOR

SPECIFICATIONS

Fire Rating

FD60 54mm 60minute to BS476:Part 22: 1987 (CERTIFIRE CF179).

Construction

Moulded wood fibre face with hardwood stiles and rails.
FD60 Magnesium Oxide Board core.

Door Codes

Arlington 6 panel smooth (enhanced bead detail)	ARLFD
Atherton 4 panel smooth	ATHFD
Bostonian 6 panel woodgrain	BTNFD
Cambridge 2 panel smooth	CAMBFD
Camden 2 panel woodgrain	CMNFD
Oakfield 4 panel woodgrain	OFDFD
Rockport® 5 panel smooth	ROCKFD
Newark woodgrain	NEWAFD
Linea smooth	LINEFD
Cube smooth	CUBEFD
Newbridge smooth	NEWBFD

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.0mm die-formed moulded wood fibre skin.

Components

Stiles:	Hardwood min 48mm (nominal width)
Rails:	Hardwood min 48mm (nominal width)
Core:	Magnesium Oxide Board
Lockblock:	N/A
Lipping:	N/A

Lock Area

Locks and handles may be fitted centrally in height either side of the door, maximum dimensions specified on installation instructions provided.

Finish

Supplied white primed for paint or stain finish on site.

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge. The top of the door is not allowed to be trimmed due to the BWF-Certifire certification label and manufacturing identifications.

Installation Note

The doors have been tested to BS476 pt 22:1987 and are approved by BWF-Certifire of being capable of achieving 60 minute fire resistance when fitted in accordance with the installation instruction delivered with every door.

All doors must be fitted with intumescent strips to the top and sides of the door leaf or frame.

Cutting of apertures or glazing on site is not permitted and invalidates the fire certification.

Third party BWF-Certifire licensed processors are able to complete this ancillary work when required.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

