

MOULDED PANEL HEAVYWEIGHT CORE – INTERNAL DOOR

SPECIFICATIONS

Construction

Moulded wood fibre face with softwood stiles and rails.
Heavyweight flaxboard core.

Door Codes

Arlington 6 panel smooth (enhanced bead detail)	ARLHW
Atherton 4 panel smooth	ATHHW
Bostonian 6 panel woodgrain	BTNHW
Cambridge 2 panel smooth	CAMBHW
Camden 2 panel woodgrain	CMNHW
Oakfield 4 panel woodgrain	OFDHW
Rockport® 5 panel smooth	ROCKHW
Newark woodgrain	NEWAHW
Linea smooth	LINEHW
Cube smooth	CUBEHW
Newbridge smooth	NEWBHW

Moisture Content

10% (+/-2%) in accordance with BS:EN942.

Facings

3.0mm die-formed moulded wood fibre skin.

Components

Stiles:	Softwood min 28mm (nominal width)
Rails (outer):	Softwood min 28mm (nominal width)
Rails (inner):	Softwood min 28mm (nominal width)
Core:	Flaxboard
Lockblock:	N/A
Lipping:	N/A

Lock Area

Locks and handles maybe fitted centrally in height either side of the door.

Finish

Supplied white primed for paint finish on site. Woodgrain doors can be supplied fully finished in white semi gloss paint as an optional extra (+P). or undercoated (W).

Maximum Trim

6mm from the bottom of the door and 4mm from each vertical edge.
The top of the door should not be trimmed due to the manufacturing identifications.

Maintenance

We recommend wiping down all surfaces with a clean damp cloth at least 4 times per year. We do not recommend using cleaning solutions or abrasive materials as this will damage the door.

Re-decorate the door as necessary always following the paint manufacturer's instructions.

